# TECHNICAL SPECIFICATION



# M600 Series - M632 - Box of 10 - FFP3V - MOULDED DISPOSABLE DUST MASK

M632 - - FFP3V - MOULDED DISPOSABLE DUST MASK / BGZ130-000-A00



#### **DESCRIPTION**

Moulded disposable respirator with comfort foam surround, adjustable nose clip, four-point adjustable harness and low resistance exhalation valve.

# OPTIONS

M632 - - FFP3V - MOULDED DISPOSABLE DUST MASK (BGZ130-000-A00)

# SAFETY STANDARDS

EN 149















#### **SPECIFICATIONS**

Classification

FFP3 (Filtering Facepiece Particulate, Valved)

Usage

NR (Non-Reusable)

Minimum Filtration Efficiency 99% For FFP3 Rated

Nominal Protection Factor

50

Mask Design

Moulded



4 Point Harness adjustment system

Yes

Latex free

Yes

Filter Shelf Life

5 Years



Filter Type

P (Protects Against Solid and Liquid Aerosols)



Activated Carbon Layer

No

Maximum Total Inward Leakage (TIL)

2%

**UK Assigned Protection Factor** 

20



Exhalation Valve

Yes - Polystyrene exhalation valve with rubber diaphragm



Nose Bridge

Moulded in mask

Mask Material Polypropylene



**Product Weight** 

22g (Approx) Each Mask

#### **FEATURES**



#### **Exhalation Valve**

Low resistance exhalation valve for easy breathing.



#### 4-Point Adjustable Straps

Metal free, 4-point adjustable straps create a firm and adaptable fit.



#### Foam Padded Nose Bridge

A mouldable nose bridge and 360° foam area around the inside provide comfort and a firmer fit.

# RANGE



# DOWNLOADS


Image Pack (ZIP)

doc-m632.pdf (PDF)

doc-m632.pdf (PDF)













inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 21 Aug 2023 / Copyright 2018 - 2023. JSP Limited. All Rights Reserved.