

An ISO 9001 : 2015 Certified Company

Retractable Block Polymer Casing with G.I. wire Rope & EA

Ref: SF-RFAE-5, SF-RFAE-6, SF-RFAE-10

Robust, light weight and Durable Polymer, casing made from high impact strength nylon. Has a Swivel Anchorage eye at one end: and a Swivel Steel Snap Hook SF-1404 with energy absorber (EA-4400) at the retractable end.

DESIGN

- Quick activating breaking mechanism component
- Robust & durable plastic casing
- Has swivel anchorage eye at anchorage end
- Steel snap hook at retractable end (Our ref. SF-1404 as per ANSI Z359.12-2009 & EN 362:2002 gate strength 3600 lbs.
- Galvanized steel wire rope.

LENGTH

- 5 mtr, 6 mtr & 10 mtr.

CABLE

- Material: Galvanized steel wire rope 4.8 mm.
- Minimum Breaking Strength: 12 KN

WEIGHT

- SF-RFAE-5 :- 4.050 kg ± 0.100 kg
- SF-RFAE-6 :- 4.150 kg ± 0.100 kg
- SF-RFAE-10 :- 4.550 kg ± 0.100 kg

USER CAPACITY

- User Capacity: 100 kg Max.

RELEVANT STANDARD

- Meets or Exceeds EN 360 : 2002; VG11 RFU # 11.060.

