

# TECHNICAL SPECIFICATION



## 2m Webbing Anchorage Sling

2m Webbing Anchorage Sling / FAR0504



### DESCRIPTION

2m Webbing Anchorage Sling made from 20mm wide polyester webbing. 25kN breaking strength.

### OPTIONS

**2m Webbing Anchorage Sling (FAR0504)**

### SAFETY STANDARDS

EN 795



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 2 Jan 2023 / Copyright 2018 - 2023. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

Length  
2m

Material  
20mm Wide Polyester Webbing



Rated Weight / Load  
20kN Breaking Strength



Product Weight  
250g

## DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-far0504-far0514.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 2 Jan 2023 / Copyright 2018 - 2023. JSP Limited. All Rights Reserved.

