TECHNICAL SPECIFICATION



Flexinet® Mask FFP2V (822)

Box of 10 / BER122-201-A00



DESCRIPTION

The Flexinet[™] disposable mask has an ergonomic 3D design to fit most face shapes, with extremely low breathing resistance and mesh outer shell to help the mask retain its shape.

• Medium efficiency (94% minimum) filtering.

OPTIONS

Box of 10 (BER122-201-A00)

SAFETY STANDARDS

EN 149















SPECIFICATIONS

Classification

FFP2 (Filtering Facepiece Particulate)

Usage

NR (Non-Reusable)



Activated Carbon Layer

No

Maximum Total Inward Leakage (TIL)

8%

UK Assigned Protection Factor

10



Exhalation Valve

Advanced Valve



Nose Bridge

Moulded

Metal Free

Yes

Filter Shelf Life

5 Years



Product Weight

22g



Filter Type

P (Protects Against Solid and Liquid Aerosol)



(D) Resistance to dust clogging

Yes - D marking = passes optional clogging test

Minimum Filtration Efficiency 94% For FFP2 Rated

Nominal Protection Factor

12

Mask Design

Mesh Outer Shell

Toggle Harness adjustment system

Yes

Latex free

Yes

Mask Material

Polyproproylene



BSI Kitemark

Yes

FEATURES



Comfort

A 360° comfort foam area around the inside of the mask provides a perfect fit.



Advanced Valve

Advanced design valve allows for lower breathing resistance.



Protective Grill

Flexible cover to protect and retain the shape of the mask and protect the wearer against possible damage to the filter.

RANGE



DOWNLOADS

Image Pack (ZIP)

doc-olympus-800-series-822.pdf (PDF)





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



